

# T E S T C E R T I F I C A T E

**CT-20-06-03-03**

**Product:** MDF faced  
Product name: Beschichtete MDF EN16516  
(Specialty faced MDF - Facing: Aluminium, HPL, Acrylic)  
Resin recipe: UF  
Production date: 2020-03-12  
Batch: 001  
Thickness: 18 mm

**Manufacturer:** Kronospan CRO d.o.o.  
Slavonska cesta 17  
43000 Bjelovar  
Croatia

**Order:** Determination of the formaldehyde emission of specialty faced MDF according to chamber method DIN EN 16516

**Test method:** Formaldehyde emission according to chamber method DIN EN 16516

**Test report:** Test report 2119165/E1-2020/MFF/2020 dated 29 May 2020

**Test result:** The formaldehyde emission of the above product determined according to DIN EN 16516 is 27 µg/m<sup>3</sup> after 28 days of testing.

Therefore, the tested specialty faced MDF fulfils the requirements of the German Chemical Prohibition Ordinance Appendix 1 to §3 dated 2017-01-20 in connection with „Bekanntmachung analytischer Verfahren für Probenahmen und Untersuchungen für die in Anlage 1 der Chemikalien-Verbotsverordnung genannten Stoffe und Stoffgruppen vom 5. November 2018“ published on 26 November 2018, BAnz AT 26.11.2018 B2.

Dresden, 03 June 2020



Head of laboratory



Engineer in charge